



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

July 29, 2015

Mrs. Abigail T. D. Wacek  
Regulatory Agent For: King Technology, Inc.  
Technology Sciences Group, Inc.  
1150 18<sup>th</sup> Street, NW; Suite 1000  
Washington, DC 20036

Subject: Notification per PRN 98-10 – Minor Label Changes  
Product Name: Spa Chlorine Disinfectant  
EPA Registration Number: 53735-14  
Application Date: July 1, 2015  
Decision Number: 506946

Dear Mrs. Wacek:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

If you have any questions, you may contact Killian Swift at 703-308-6346 or via email at [Swift.Killian@epa.gov](mailto:Swift.Killian@epa.gov).

Sincerely,

A handwritten signature in blue ink that reads "Wanda J. Fuller, for".

Demson Fuller, Product Manager 32  
Regulatory Management Branch II  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

[All text in brackets {xxx} is optional and may or may not be included on a final label.]

[All text in braces [xxx] is administrative and will not appear on a final label.]

**NOTIFICATION**

53735-14

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

07/29/2015

**[MASTER LABEL]**

**SPA CHLORINE DISINFECTANT  
Prefilled Chlorine {Spa} {Hot Tub} Sanitizer**

Active Ingredients:

1,3-dichloro-5, 5-Dimethylhydantoin.....81.1%

1,3-dichloro-5-ethyl-5-methylhydantoin.....16.1%

Other Ingredients:..... 2.8%

Total: .....100.0%

**Keep Out of Reach of Children**

**DANGER**

**{SEE {FIRST AID} AND PRECAUTIONARY  
STATEMENTS ON BACK PANEL}**

**{See Enclosed Instruction Manual for Complete Directions for Use}**

EPA Reg. No.: 53735-14

EPA Est. No.: xxxxx-xx

Distributed By: King Technology, Inc.  
530 11<sup>th</sup> Ave S  
Hopkins, MN 55343

Net Wt.: xxx grams

**FIRST AID:** If in Eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice. If on Skin or Clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. ~~If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.~~ If Swallowed: Call poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person. Have the product container or label with you when calling a poison control center or doctor, or going for treatment. If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice. Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.

**IN CASE OF MEDICAL EMERGENCY CALL 1-800-424-9300.**

#### **PRECAUTIONARY STATEMENTS:**

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS:** DANGER: Corrosive. Causes irreversible eye and skin damage. May be fatal if swallowed. Irritating to nose and throat. Avoid breathing dust and fumes. Do not get in eyes, on skin or on clothing. Wear goggles or safety glasses and rubber gloves when handling product. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse.

**PHYSICAL AND CHEMICAL HAZARDS:** STRONG OXIDIZING AGENT: Do not mix with other chemicals. Mix only with water. Never add water to product. Always add product to large quantities of water. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire and explosion. Contamination with moisture, organic matter or other chemicals will start a chemical reaction and generate heat, hazardous gas, possible fire and explosion. In case of contamination or decomposition, do not reseal container. If possible, isolate container in open air or well-ventilated area. Flood area with large volumes of water.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish and aquatic organisms.

**Note:** Buyer assumes all responsibility for safety and use not in accordance with directions.

## [Product Description and Directions for Use with In-Line and Floating System]

**Product Description:** The SPA CHLORINE DISINFECTANT is {a} {an} {innovative} {revolutionary} way to maintain a low level of {chlorine} {sanitization} {disinfection} {tailor made} {perfect} for use with the Pool Frog Mineral Reservoir that reduce{s} chlorine use. {The SPA CHLORINE DISINFECTANT {may be} {is} used with the Pool Frog Mineral Reservoir in the {In-line {Spa} {Hot Tub} System} {or} {Floating {Spa} {Hot Tub} System} for weeks of low level {chlorine} {sanitization} {disinfection} protection.} Together they make {spa} {hot tub} care a breeze with up to 75%\* less chlorine\* so the water feels softer and looks crystal clear with no smelly odors, no adding chlorine daily and no weekly shocking. Swimsuit colors stay bright and {spa} {hot tub} surfaces maintain their brilliance longer. {Experience the difference Pool Frog Mineral Reservoir and SPA CHLORINE DISINFECTANT will make in your {spa} {hot tub}.}

**Directions for Use:** It is a violation of federal law to use this product in a manner inconsistent with its labeling.

For use in {spas} {hot tubs} up to {500} {600} gallons. Use the SPA CHLORINE DISINFECTANT with the Pool Frog Mineral Reservoir in the {In-Line System} {or} {Floating System}. Ensure all {spa} {hot tub} equipment is working properly. The pump and filter should be operated for at least 3 hours per day. Clean filter following manufacturer's directions. May be used with a previously filled {hot tub} {spa} unless it was sanitized with bromine. Then drain and fill {spa} {hot tub} with fresh water. Balance the water according to the water balance guidelines with pH between 7.2 – 7.8 and total alkalinity at 60 to 120 ppm. {After balancing,} {Begin with} {establish} a free chlorine residual of 0.5 to 1.0 ppm in the {spa} {hot tub} {with} {from Frog Jump Start start-up shock} {or} an EPA approved {spa} {hot tub} chlorine shock following the directions for that product. {When using other products as outlined in directions for this product, always follow directions on those products.}

**Setting the Output:** The SPA CHLORINE DISINFECTANT is prefilled and adjustable to meet the needs of each {spa} {hot tub} use. {Typically In-Line System users will begin on setting # {while Floating System users will begin on setting #} and adjust up or down from there.} {Hold the bottom and turn the top of the cartridge until the correct number appears in the setting window} . {See the setting chart in the manual for best results.}

{Then use SPA CHLORINE DISINFECTANT in{to} {one of} the following system{s}:}

**{The In-line Mineral {Spa} {Hot Tub} System} {Inserting the Cartridge}:** Open cap of Inline System, push down and turn cartridge holder counter-clockwise to unlock. Pull holder out. Snap cartridge into {lower} {bottom} section {marked {"Bromine} {or Chlorine} {or SmartChlor} "}. The Pool Frog Mineral Reservoir cartridge will be in the

top section marked "Minerals." Make sure to line up indent on cartridge with raised line on holder. After cartridge is snapped in, replace holder by lining up arrow on holder with arrow on system lip, push down and rotate clockwise to lock in place. Replace cap.}

**{The Floating Mineral Spa System} {Using the SPA CHLORINE DISINFECTANT}:**

{Push the cartridge into the bottom opening of the Floating Spa System} and place entire system in the {spa} {hot tub} water.}

{Must be used with} {When using} the Pool Frog Mineral Reservoir Cartridge, {and} maintain a free chlorine level of 0.5 – 1.0 ppm. ~~{Initially}~~ {For the first week} monitor free chlorine levels daily and adjust the cartridge up or down by one setting per day until the desired chlorine level is achieved. Adjusting to a higher setting will increase the chlorine output while a lower setting will decrease it.} {If your Test Strip consistently shows lighter than the {free} {active} chlorine block on the Test Strip label, then adjust your setting up by one number. If showing a darker color, lower the setting one number.}}

**Replacing the Cartridge:** When empty the Test Strips will show a lighter color than the out indicator on the Test Strip label. When this happens remove the SPA CHLORINE DISINFECTANT from the system, drain the water and shake slightly to see if it is empty. Follow disposal instructions and replace with a new SPA CHLORINE DISINFECTANT. Do not discard or recycle cartridge if a small amount of chlorine remains. {Place in the {spa} {hot tub} to float on its own} {or} {Place back in the in-line system} until completely empty.

Shock the {spa} {hot tub} when you replace SPA CHLORINE DISINFECTANT or {once a month}. {Add clarifier occasionally if the water should become cloudy.} With SPA CHLORINE DISINFECTANT less shocking is required because {of the chlorine {bank} {reserve} (measured as total chlorine) that is {ready to use} {automatically converted to {active} {free} chlorine} when needed} {it maintains a consistent level of sanitization even when people enter the {spa} {hot tub}}.

**REENTRY into treated {spas} {hot tubs} is prohibited above levels of 5 ppm available {free} chlorine as measured by a suitable test kit due to risk of bodily injury.**

## Product Description and Directions for Use with Floating/Flipping System

**Product Description:** The SPA CHLORINE DISINFECTANT is {a} {an} {innovative} {revolutionary} way to maintain a low level of {chlorine} {sanitization} {disinfection} {tailor made} {perfect} for use with {Pool Frog Mineral Reservoir} that reduce{s} chlorine use. Together they make {spa} {hot tub} care a breeze with up to 75%\* less ~~chlorine-chlorine~~\*so the water feels softer and looks crystal clear with no smelly odors, no adding chlorine daily and no weekly shocking. Swimsuit colors stay bright and {spa} {hot tub} surfaces maintain their brilliance longer.

**Directions for Use:** It is a violation of federal law to use this product in a manner inconsistent with its labeling.

For use in {spas} {hot tubs} up to {500} {600} gallons. Use only with the Pool Frog Mineral Reservoir. Ensure all {spa} {hot tub} equipment is working properly. Operate the pump and filter for at least 3 hours per day. Clean filter following manufacturer's directions. May be used with a previously filled {spa} {hot tub} unless it was sanitized with bromine. Then drain and fill {spa} {hot tub} with fresh water.

**Start-up:** Balance the water according to the water balance guidelines with pH between 7.2 – 7.8 and total alkalinity at 60 to 120 ppm. {Begin with} {Establish} a free chlorine residual of 0.5 to 1.0 ppm in the {spa} {hot tub} {from} {with} {Frog Jump Start start-up shock} {or} {an EPA approved {spa} {hot tub} chlorine shock} {or by other means} following the directions for that product. {When using other products as outlined in directions for this product, always follow directions on those products.}

### To assemble:

- Remove outer packaging
- Peel off {protective} {seal} {label} from the flat part of the SPA CHLORINE DISINFECTANT cartridge
- Align arrows on {color} mineral cartridge and {color} chlorine cartridge
- Push together and twist to lock
- {Set the dial on the chlorine cartridge (see Setting Chart in manual)}
- Place entire system in the {spa} {hot tub} water.
- ~~{Weekly}~~ {Periodically} test the water to ensure pH balance and a 0.5 to 1.0 ppm ~~free~~ chlorine level
- ~~{Adjust cartridge setting if needed }~~
- Shock the {hot tub} {spa} when replacing SPA CHLORINE DISINFECTANT or once a month

**Replacing the Cartridge:** When {the system flips over} {or} {the Test Strip shows a lighter color than the out indicator on the Test Strip label}, replace the SPA CHLORINE DISINFECTANT by rotating the two cartridges until the arrows align and pull apart. Drain the water from the old SPA CHLORINE DISINFECTANT and shake slightly to see if it is empty. Follow disposal instructions and replace with a new SPA CHLORINE DISINFECTANT. Do not discard or recycle cartridge if a small amount of

chlorine remains. Place in the {spa} {hot tub} to float on its own until completely empty.

{Additional Information:

- Keeping the pH in the proper range of 7.2 to 7.8 will allow SPA CHLORINE DISINFECTANT to keep the free chlorine level between 0.5 and 1.0 ppm with little adjusting. If your Test Strip consistently shows lighter than the {free} {active} chlorine block on the Test Strip label, then adjust your setting up by one number. If showing a darker color, lower the setting one number.}
- With SPA CHLORINE DISINFECTANT less shocking is required because {of the chlorine {bank} {reserve} that is {ready to use} {automatically converted to {active} {free} chlorine} when needed} {it maintains a consistent level of sanitization even when people enter the {spa} {hot tub}.}

**REENTRY into treated {spas} {hot tubs} is prohibited above levels of 5 ppm available {free} chlorine as measured by a suitable test kit due to risk of bodily injury.**

**[The following copy is engraved into the plastic container]**

Not a toy

No es un juguete

Keep Out of Reach of Children

DANGER

EPA Reg. No.: 53735-14{-xxxxx}

{kingtechnology.com} [OR] {heycoolpool.com}

{U.S. & Foreign patents pending}

{Patents} {Patent Pending}: {kingtechnology.com/IP} [OR] {heycoolpool.com/IP}

**STORAGE AND DISPOSAL:** Do not contaminate food or feed by storage and disposal.

**Pesticide Storage:** Keep this product dry in original tightly closed container when not in use. Store in a cool, dry, well-ventilated area away from heat. Moisture may decompose this product and cause a violent reaction leading to fire and explosion. In case of decomposition, isolate container if possible and flood area with large amounts of water to dissolve material before discarding this container

**Container Handling:** Non-refillable container. Do not reuse or refill this container. Offer for recycling if available. Rinse thoroughly before recycling or discarding in trash.

[Disclaimers]

\* Compared to the ANSI minimum recommended chlorine level of 2.0 ppm for a residential {spa} {hot tub}.

\*\* Compared to daily shocking or shocking each time the {spa} {hot tub} is used

## **[Operational Instructions for In-Line Mineral Spa System]**

**[All text is optional]**

### **In-Line System Operating Instructions**

#### **Congratulations!**

{Your {spa} {hot tub} came with a complete mineral and chlorine {sanitation} {disinfecting} {disinfection} system. When using the {patented} Pool Frog Mineral Reservoir with the proprietary SPA CHLORINE DISINFECTANT, you'll enjoy your {spa} {hot tub} more with less work and less chlorine.

#### **Less Work Because:**

- The Frog Mineral {System} {Technology} {Formula}+ continuously works to control bacteria for four full months.
- Cartridges last longer to eliminate daily maintenance.
- Cartridges are pre-filled for no measuring or mess.
- Simply adjust to your setting and relax for weeks {until it's time to replace the {chlorine} cartridge}.

#### **Less Chlorine Because:**

- With minerals in the water, chlorine use is cut by up to 75%.\*
- It's precisely metered over {2} {3}-4 weeks {so it lasts longer than daily spoon feeding} (on a 350 gallon {spa} {hot tub} with average use).
- With minerals and low levels of chlorine, the water feels softer.
- The system reduces odors and leaves the water crystal clear.}

{Welcome to Fresh Mineral Water with SPA CHLORINE DISINFECTANT technology courtesy of Frog. This {spa} {hot tub} water care system destroys bacteria to keep your {spa} {hot tub} clean with less work and up to 75% less chlorine.\* There are two cartridges – the top one holds our {patented} mineral formula while the bottom one has a different kind of chlorine that is smart about when it's needed and when it's not. Its revolutionary formula creates a bank of chlorine that is {equivalent to} {detected as} {read as} {measured as} a total chlorine reading on a test strip. Over time, this bank automatically converts to {active} {free} chlorine when needed to take care of the bacteria and contaminants in the water. The {active} {free} level stays at a low 0.5 ppm which is tailor made for use with Frog minerals that reduce chlorine use up to 75%\*.

Simply set and insert into the bottom section of the In-Line System. Everything is prefilled and contained for no mess, no guess {and} no stress {spa} {hot tub} care.


You're going to love your System. If you have any questions, contact our customer service representatives at **800-222-0169**.

\* Compared to the minimum ANSI recommended chlorine level of 2.0 ppm for a {spa} {hot tub}.

#### **Let Us Dissect This System For You: The complete In-Line System**

The In-Line System is made up of (A) a cap that is easily distinguishable among the fittings on the top {rim} {edge} of the {spa} {hot tub}, (B) a cartridge holder that pulls out of the system, (C) a mineral cartridge that helps control bacteria in the water and (D) a {chlorine} {sanitizer} {disinfectant} SPA CHLORINE DISINFECTANT cartridge that helps support the


minerals while oxidizing contaminants like body oils {and ammonia compounds responsible for smelly chloramines}. The cartridges are adjustable to meet your specific {spa} {hot tub} water care needs.



Cut-away view of cartridges snapped into holder and placed into the In-Line System.

**Start Up** - Follow all directions from your {spa} {hot tub} manufacturer on filling and balancing the water in your {spa} {hot tub}. Standard guidelines for balancing the water are as follows:

Water Balance Guidelines	
pH:	7.2-{7.6} {7.8}
Total Alkalinity:	60-120 ppm
Calcium Hardness:	150-400
Total Dissolved Solids:	<1500
*Free Chlorine:	0.5-1.0 ppm



\*NOTE: Free chlorine levels are reduced up to 75%\* when using Frog minerals


- Use Test Strips {that came with your maintenance kit} or a test kit to routinely check your pH, Total Alkalinity and Calcium Hardness. Once the SPA CHLORINE DISINFECTANT Cartridge is in the system, it will maintain the free chlorine level of 0.5 – 1.0 ppm. pH is affected by {weather} bather load, chemicals used, evaporation and the make-up of your source water.
- {Use a metal out or sequestering agent if fill water is high in metals. Wait 24 hours before continuing start up.}
- **Very Important!** {Shock {spa} {hot tub} to establish a 0.5-1.0 ppm free chlorine residual. Add directly to {spa} {hot tub} following manufacturers' directions.} {Before using cartridges, {establish} {ensure there is} an initial residual of 0.5-1.0 ppm free

chlorine with {Frog Jump Start start-up shock {that came in this package}} {a chlorine shock.} {{For best results use Frog Jump Start} {This} start-up {spa} {hot tub} shock packet {that} quickly dissolves with an effervescent fizzing action – one packet per 500 gallons} {Do not use a non-chlorine shock as it cannot establish a chlorine residual.} Do NOT add any shock product through the In-Line System. Use {the appropriate chlorine test strips or kit and follow manufacturer’s instructions.} {Test Strips {that came in the package} to accurately maintain the reduced 0.5 to 1.0 ppm {free} chlorine level following the label directions carefully}.


- When {spa} {hot tub} reaches operating temperature per your {spa} {hot tub} manufacturer’s directions, remove the shrink wrap from both cartridges. Set the mineral and {chlorine} {sanitizer} {disinfectant} {SPA CHLORINE DISINFECTANT} cartridges according to directions on [phrase will be inserted here to direct the user to the place on the market label that the {spa} {hot tub} care procedures can be found] and insert them into the System.

### Replacing Cartridges


- Open cap of In-Line System and set aside. DO NOT OPEN CAP WHILE JETS ARE ON.
- Remove holder by pushing down and turning counterclockwise before pulling out.
- Remove spent cartridges by pushing bottom out through openings in back of holder. Then grab cartridge and pull out.
- Snap the Pool Frog Mineral Reservoir into the area marked “Minerals” (top portion) and the SPA CHLORINE DISINFECTANT Cartridge into the area marked {“Bromine} {or Chlorine”} {or SmartChlor”} (bottom portion) making sure to line up the indentation at the top of the cartridges with the raised area on the holder.



- Slowly insert holder into system (see diagrams). Line up holder arrow-① with system arrow-②. Push down until holder tabs-③ go past system tabs-④ and turn holder to the right (clockwise) until it stops. To ensure a locked position, attempt to pull holder up. If it stays in place, the lock is secure.



- Begin regular {spa} {hot tub} care procedures (see page #) as soon as start-up is complete.



### **Adjusting and When to Replace Pool Frog Mineral Reservoir:**

- Set the {color} Pool Frog Mineral Reservoir wide open on #6 by holding the bottom and turning the top until the number 6 appears in the setting window. No further adjustments are necessary.
- The Pool Frog Mineral Reservoir must be replaced every 4 months. After four months of use, or when draining and refilling the {spa} {hot tub} with fresh water, discard Pool Frog Mineral Reservoir in trash even if, upon shaking, it appears there is spent media left inside. Once wetted the time released minerals in the cartridge are effective up to four months. Do not attempt to reuse the product once removed from the {spa} {hot tub}. {For ease in remembering, mark your calendar with the Reminder Stickers included with this manual.} {See {spa} {hot tub} manufacturer's draining recommendations.}

### **Adjusting and When to Replace SPA CHLORINE DISINFECTANT:**

{As every {spa} {hot tub} is different, finding the right setting for the {color} {chlorine} {sanitizer} {disinfectant} {SPA CHLORINE DISINFECTANT} cartridge will require monitoring your usage for the first week or two.} {SPA CHLORINE DISINFECTANT will maintain a low 0.5 to 1.0 ppm chlorine level as long as the pH stays within 7.2 and 7.8 so there is little need to adjust the cartridge setting.}

Begin with an initial setting based on the chart {below} {on page #} and for one week monitor free chlorine levels daily or before each use, adjusting the cartridge by one setting per day until a 0.5-1.0 ppm level has been achieved.

Use Test Strips that show the exact active (free) chlorine color you should match when using Frog minerals. If the water test shows lighter than that color, the chlorine level is low. To adjust cartridge, remove from system and turn to the next highest setting. If the water test shows darker than that color, the chlorine level is high so the setting should be decreased by one number. If the chlorine bank (total) reading is lighter than the color on the bottle, check the cartridge {to see if it is} {as it may be} empty.

{If using standard test strips, the free chlorine level should be 0.5 ppm {to 1.0 ppm}. The total chlorine level will be high when the {product} {cartridge} is first {used} {installed} and slowly come down over the life of the cartridge. When {it} {the total chlorine {reading}} is at 3.0 ppm, check to see if the cartridge is empty.}

The {color} {chlorine} {sanitizer} {disinfectant} {SPA CHLORINE DISINFECTANT} cartridge needs to be replaced when empty. Drain water from the cartridge and ensure it is empty before discarding in trash or offering for recycling. On {most} {the average 300-400 gallon} {spa}{s} {hot tub}{s}, it will last between {2} {3} and 4 weeks. Always maintain at least 0.5 ppm free chlorine level.

### **INITIAL START-UP SETTING**

#### **[Setting Chart Option #1]**

	<b>{Spa} {Hot Tub} Size (Gallons)</b>			
<b>Daily Filter Time</b>	<b>250-300</b>	<b>300-400</b>	<b>400-500</b>	<b>500-600</b>
One Hour	#	#	#	#
Two Hours	#	#	#	#
Four Hours	#	#	#	#
24 hour @ low flow	#	#	#	#

## [Setting Chart Option #2]

System Setting Chart	
200 Gallons	#
{250 Gallons}	#
{300 Gallons}	#
{350 Gallons}	#
{400 Gallons}	#
{450 Gallons}	#
{500 Gallons}	#
600 Gallons	#

{NOTE: The more you use the {spa} {hot tub}, for instance when you first {get it} {own it}, the greater the setting to achieve at least 0.5 ppm. (This may require a higher setting than what is listed in the chart.) If usage decreases or the chlorine level is greater than 1.0 ppm, lower the setting.}

### **Regular {Spa} {Hot Tub} Care Procedures:**

Always follow the directions for operating your particular {spa} {hot tub}.

- Run filtration system as directed by your {spa} {hot tub} manufacturer to maintain proper water flow through the In-Line System {or at least 3 hours per day}.
- Periodically test the water to maintain pH, total alkalinity, {calcium hardness} and a 0.5 to 1.0 ppm {active} {free} chlorine level {with the precise Test Strips that include special directions for using with Frog products}.
- Maintain {at least a 0.5 ppm of} {a} free chlorine {level that matches the color shown on the Test Strip bottle} {at all times}. The SPA CHLORINE DISINFECTANT forms a chlorine bank that is measured as total chlorine on a standard test strip/kit. This chlorine bank readily shifts to free chlorine as needed to maintain {a desirable} {our recommended} low level of chlorine {available for disinfection}. {Based on average {spa} {hot tub} usage,} chlorine will last {on average} {about} {up to} {2} {3}-4 weeks for {spas} {hot tubs} {up to} {of} {350} {400} {500} {600} gallons.}
- Shock the {spa} {hot tub} with {granular chlorine or} {a non-chlorine shock} {when you replace the SPA CHLORINE DISINFECTANT Cartridge or once a month} {if the water looks cloudy} {and/or add a {spa} {hot tub} clarifier according to label directions}. With SPA CHLORINE DISINFECTANT, far less shocking is required compared to standard water treatments that require weekly shocking or shocking after every use.
- Remember to replace your Pool Frog Mineral Reservoir and SPA CHLORINE DISINFECTANT as directed under "Adjusting and When to Replace".
- Lubricate o-ring twice a year with a silicone lubricant.

**[Operational Instructions for Floating Mineral {Spa} {Hot Tub} System]**  
**[All text is optional]**

**Floating System Operation Instructions**

Congratulations! Your {spa} {hot tub} came with a complete mineral and chlorine {sanitation} {disinfecting} {disinfection} system. When using the {patented} Pool Frog Mineral Reservoir with the {proprietary} SPA CHLORINE DISINFECTANT, you'll enjoy your {spa} {hot tub} more with less work and less chlorine .

**Less Work Because:**

- The Mineral {System} {Technology} {Formula}+ continuously works to control bacteria for four full months.
- Cartridges last longer to eliminate daily maintenance.
- Cartridges are pre-filled for no measuring or mess.
- Simply adjust to your settings and relax {for weeks} {until it's time to replace the {chlorine} cartridge}.

**Less Chlorine Because:**

- With minerals in the water, chlorine use is cut by up to 75%.\*
- Chlorine lasts longer: {up to} {2} {3}-4 weeks on a 350 gallon {spa} {hot tub} with average use.
- With minerals and low levels of chlorine, the water feels softer.
- The system reduces odors and leaves the water crystal clear.

You're going to love your System. If you have any questions, contact our customer service representatives at **800-222-0169**.

\* Compared to the minimum ANSI recommended chlorine level of 2.0 ppm for a {spa} {hot tub}.

**{Spa} {Hot Tub} Start Up**

- Always drain and refill {spa} {hot tub} at least every 4 months.
- Clean and replace filter cartridges when dirty (*Follow manufacturer's instructions*).
- Balance water according to the chart.
- Heat water to recommended temperature before using cartridges.
- **Very Important!** Before using cartridges, establish an initial residual of 0.5-1.0 ppm free chlorine with a chlorine shock. {For best results use Frog Jump Start start-up {spa} {hot tub} shock packet that quickly dissolves with an effervescent fizzing action – one packet per 500 gallons.} {Do not use a non-chlorine shock as it cannot establish a chlorine residual.} Use {the appropriate chlorine test strips or kit and follow manufacturer's instructions.} {Test Strips to accurately maintain the reduced 0.5 to 1.0 ppm chlorine level following the label directions carefully.}
- Begin regular {spa} {hot tub} care procedures (see [phrase will be inserted here to direct the user to the place on the market label that the {spa} {hot tub} care procedures can be found]) as soon as start-up is complete.

**Water Balance Guidelines**

pH:	7.2 – {7.6} {7.8}
Total Alkalinity:	60 – 120 ppm
Calcium Hardness:	150-400
Total Dissolved Solids:	<1500
*Free Chlorine:	0.5 – 1.0 ppm

NOTE: Free Chlorine levels are reduced up to 75%\* when using Frog minerals

**Setting Cartridges**

- Set the {color} mineral cartridge to wide open on #6 by holding the bottom and turning the top until the number 6 appears in the setting window. No further adjustments are necessary.
- {As every {spa} {hot tub} is different, finding the right setting for the {color} {chlorine} {sanitizer} {disinfectant} cartridge will require monitoring your usage for the first week or two.} Begin with an initial setting based on the chart {below} {on page #} and monitor free chlorine levels daily or before each use adjusting the cartridge by one setting per day until a 0.5-1.0 ppm level has been achieved.
- Use Test Strips that show the exact active (free) chlorine color you should match when using Frog minerals. If the water test shows lighter than that color, the chlorine level is low. To adjust cartridge, remove from holder and turn to the next highest setting. If the water test shows darker than that color, the chlorine level is high so the setting should be decreased by one number. If the chlorine bank (total) reading is lighter than the color on the bottle, check the cartridge as it may be empty.
- {If using standard test strips, the free chlorine level should be 0.5 ppm {to 1.0 ppm}. The total chlorine level will be high when the {product} {cartridge} is first {used} {installed} {placed in the {spa} {hot tub}} and slowly come down over the life of the cartridge. When {it} {the total chlorine {reading}} is at 3.0 ppm, check to see if the cartridge is empty.}
- The {chlorine} {sanitizer} {disinfectant} cartridge needs to be replaced when empty. Drain water from the cartridge and ensure it is empty before discarding in trash or offering for recycling. On most {spas} {hot tubs}, it will last between {2} {3} and 4 weeks. Always maintain at least 0.5 ppm free chlorine level.

INITIAL START-UP SETTING

**[Setting Chart Option #1]**

	<b>{Spa} {Hot Tub} Size (Gallons)</b>			
<b>Daily Filter Time</b>	250-300	300-400	400-500	500-600
One Hour	#	#	#	#
Two Hours	#	#	#	#
Four Hours	#	#	#	#
24 hour @ low flow	#	#	#	#

**[Setting Chart Option #2]**

<b>System Setting Chart</b>	
200 Gallons	#
{250 Gallons}	#
{300 Gallons}	#
{350 Gallons}	#
{400 Gallons}	#
{450 Gallons}	#
{500 Gallons}	#
600 Gallons	#

NOTE: The more you use the {spa} {hot tub}, for instance when you first get it, the greater the setting to achieve at least 0.5 ppm. (This may require a higher setting than what is listed in the chart.) If usage decreases or the chlorine level is greater than 1.0 ppm, lower the setting.

### **Using the Floating System**

- Insert both cartridges into the {color} floating holder by pushing them into the openings until they stay in place.
- Let the Floating System free-float in the {spa} {hot tub}.
- When using the {spa} {hot tub}, simply remove the system, drain most of the water into the {spa} {hot tub} and set on the side of the {spa} {hot tub} inverted so all excess water drains into the holder. REMEMBER TO REPLACE {THE FLOATING SYSTEM} {IT} BACK IN THE WATER WHEN FINISHED USING THE {SPA} {HOT TUB}!

### **Replacing Cartridges**

- The Pool Frog Mineral Reservoir must be replaced every 4 months. After four months of use, or when draining and refilling the {spa} {hot tub} with fresh water, discard Pool Frog Mineral Reservoir in trash even if, upon shaking, it appears there is spent media left inside. Once wetted the time released minerals in the cartridge are effective up to four months. Do not attempt to reuse the product once removed from the {spa} {hot tub}. For ease in remembering to replace, mark your calendar with the reminder stickers provided with product.
- Replace the {chlorine} {sanitizer} {disinfectant} cartridge when empty. Drain water to ensure cartridge is empty then discard in trash {or offer for recycling}. The cartridge life will vary depending on {spa} {hot tub} size and number of users. Once your usage is determined, mark the calendar with enclosed reminder stickers.

### **Regular {Spa} {Hot Tub} Care**

- Run filtration system as recommended by your {spa} {hot tub} manufacturer.
- {Periodically test the water to maintain pH, total alkalinity, calcium hardness and a 0.5 ppm {active} {free} chlorine level {with the precise Test Strips that include special directions for using with Frog products}.
- Maintain at least a 0.5 ppm free chlorine level at all times. The SPA CHLORINE DISINFECTANT forms a chlorine bank that is measured as total chlorine on a standard test strip/kit. This chlorine bank readily shifts to free chlorine as needed to maintain {a desirable} {our recommended} low level of chlorine {available for disinfection}. {Based on average {spa} {hot tub} usage,} chlorine will last {on average} {about} {up to} {2} {3}-4 weeks for {spas} {hot tubs} {up to} {of} {350} {400} {500} {600} gallons.}
- Shock the {spa} {hot tub} {with granular chlorine or a non-chlorine shock} if the water looks cloudy or add a {spa} {hot tub} clarifier according to label directions. With SPA CHLORINE DISINFECTANT, far less shocking is required compared to standard water treatments that require weekly shocking.
- Remember to replace Pool Frog Mineral Reservoir and SPA CHLORINE DISINFECTANT as directed under "Replacing Cartridges".

# [Operational Instructions for {Spa} {Hot Tub} Floating/Flipping System] [All text is optional]

## Floating {Sanitizing} System Operation Instructions

This is not a toy. For {sanitizing} {disinfecting} {spas} {hot tubs} only!

{Welcome to Fresh Mineral Water with Smart Chlor technology courtesy of Frog. This {spa} {hot tub} water care system destroys bacteria to keep your {spa} {hot tub} clean with less work and up to 75% less chlorine.\* There are two cartridges – the top one holds our {patented} mineral formula while the bottom one has a new kind of chlorine that is smart about when it's needed and when it's not. Its revolutionary formula creates a bank of chlorine that is {equivalent to} {detected as} {read as} {measured as} a total chlorine reading on a test strip. Over time, this bank automatically converts to {active} {free} chlorine when needed to take care of the bacteria and contaminants in the water. The {active} {free} level stays at a low 0.5 ppm which is tailor made for use with Frog minerals that reduce chlorine use up to 75%\*.

Simply {connect} {the two cartridges}, {turn} {twist} the dial to set and {toss into} {plop in} the {spa} {hot tub}. Everything is prefilled and contained for no mess, no guess {and} no stress {spa} {hot tub} care. The best part is it flips over when {empty} {out} {it's time to replace {a} {the} {chlorine} cartridge}.

Register your Floating System at [KingTechnology.com](http://KingTechnology.com)

## {Spa} {Hot Tub} Start Up

- {Always} drain and refill {spa} {hot tub} at least every 4 months. If previously using bromine and switching to SmartChlor, you must drain and refill your {spa} {hot tub} first. If previously using dichlor you may convert to SmartChlor without having to drain the {spa} {hot tub}.
- Clean and replace filter cartridges when dirty (*Follow manufacturer's instructions*).
- Use Test Strips {included in the package} or a test kit to balance your pH, Total Alkalinity and Calcium Hardness {water} according to the water balance guidelines. {Once the System is in the water, it will maintain the free chlorine level.} {This {spa} {hot tub} system will {control} {maintain} the free chlorine level{of 0.5 – 1.0 ppm}.} pH is affected by {weather} bather load, chemical usage, evaporation and the make-up of your source water.

### Water Balance Guidelines

pH:	7.2 – {7.6} {7.8}
Total Alkalinity:	60 – 120 ppm
Calcium Hardness:	150-400
Total Dissolved Solids:	<1500
*Free Chlorine:	0.5 – 1.0 ppm

NOTE: Free Chlorine levels are reduced up to 75%\* when using Frog minerals

- Heat water to recommended temperature before using cartridges.
- **Very Important!** Before using cartridges, {establish} {ensure there is} an initial residual of 0.5-1.0 ppm free chlorine with {Frog Jump Start start-up shock {included in this package}} {a chlorine shock}. {{For best results use Frog Jump Start} {This} start-up {spa} {hot tub} shock packet {that} quickly dissolves with an effervescent fizzing action – one packet per 500 gallons.} {Do not use a non-chlorine shock as it cannot

establish a chlorine residual.) Use {the appropriate chlorine test strips or kit and follow manufacturer's instructions} {Test Strips {included in this package} to accurately maintain the {reduced} {low} 0.5 {-1.0} ppm chlorine level following the label directions carefully}.

## **Using the Floating System**

1. Remove {the} {outer} packaging from both the mineral and chlorine cartridges {and while holding the cartridge over the {hot tub} {spa} remove the {protective} {peel off} {tear off} seal {label} on the chlorine cartridge and allow any loose {fines} {particles} to fall into the water}. NOTE: Small mineral particles may have dislodged from the mineral cartridge in shipping. Simply discard {those particles} in trash. Bring the two cartridges together and line up the arrows on the chlorine cartridge with the unlock symbol on the mineral cartridge. {Push together and twist to {lock} {the lock symbol} {the desired setting number.} {Rotate the two cartridges {until you {hear} {feel} the {safety} {locking} {tab} {two cartridges} click into place} {approximately 90° to lock in place}.
2. **{Setting the Chlorine Output}**
  - {Twist the mineral cartridge opposite of the chlorine cartridge until the setting number for your {spa} {hot tub} size is lined up with the arrow (see chart {below} {on page #}).} {Twist the dial on the {bottom} {chlorine} cartridge to the setting {number} for your {spa} {hot tub} size (see chart).} {Start with the {factory} {middle} {center} {medium} setting.} {SPA CHLORINE DISINFECTANT will maintain this level as long as the pH stays within 7.2 and 7.8 so there is {no} {little} need to adjust the cartridge setting}
  - For the first week or so test the water daily with Test Strips that show the exact active (free) chlorine color you should match when using Frog minerals. If the water test shows lighter than that color, the chlorine level is low, {Twist the two cartridges opposite each other to reach one setting higher.} {Turn the dial on the chlorine cartridge to the next highest setting.} If the water test shows darker than that color, the chlorine level is high so the setting should be decreased by one number. Even at the {lowest} {off} setting {of 0} there will be some chlorine released into the {spa} {hot tub}. If the chlorine bank (total) reading is lighter than the color on the bottle, check the chlorine cartridge as it may be empty.
  - {If using standard test strips, the free chlorine level should be 0.5 ppm {to} 1.0 ppm}. The total chlorine level will be high when the product is first {used} {installed} {placed in the {spa} {hot tub} and slowly come down over the life of the cartridge. When {it} {the total chlorine {reading}} is at or below 3.0 ppm, the system should be flipping over so check to see if the cartridge is empty.}
  - {The {color} {chlorine} {sanitizer} {disinfectant} cartridge needs to be replaced when empty. Drain water from the cartridge and ensure it is empty before discarding in trash or offering for recycling. Always maintain at least 0.5 ppm free chlorine level.}

## INITIAL START-UP SETTING

[Setting Chart Option #1]

	{Spa} {Hot Tub} Size (Gallons)			
Daily Filter Time	250-300	300-400	400-500	500-600
One Hour	#	#	#	#
Two Hours	#	#	#	#
Four Hours	#	#	#	#
24 hour @ low flow	#	#	#	#

[Setting Chart Option #2]

System Setting Chart	
200 Gallons	#
{250 Gallons}	#
{300 Gallons}	#
{350 Gallons}	#
{400 Gallons}	#
{450 Gallons}	#
{500 Gallons}	#
600 Gallons	#

{NOTE: The more you use the {spa} {hot tub}, for instance when you first {get it} {own it}, the greater the setting to achieve at least 0.5 ppm. (This may require a higher setting than what is listed in the chart.) If usage decreases or the chlorine level is greater than 1.0 ppm, lower the setting.}

- Once set, simply toss it into the {spa} {hot tub}

[graphic callouts:] {insert color} Top Half: mineral cartridge, {insert color} Bottom Half: chlorine cartridge, Setting {#} on SPA CHLORINE DISINFECTANT cartridge, Twist {dial on bottom of chlorine cartridge}

- Test the water periodically with Test Strips to maintain pH, total alkalinity, calcium hardness and ensure SPA CHLORINE DISINFECTANT is maintaining a 0.5 ppm active (free) chlorine level. {Based on average {spa} {hot tub} usage,} chlorine will last {on average} {about} {up to} {2} {3}-4 weeks for {spas} {hot tubs} {up to} {of} {350} {400} {500} {600} gallons.
- Follow regular {spa} {hot tub} care procedures on {page #} {below}.

### Replacing the Chlorine Cartridge

When the {product} {chlorine cartridge} is almost empty {it} {the system} will {begin to} slowly {flip} {roll} over giving you {a day or two} notice that it's about time to replace. If it stays on its side longer than a day or two, pull unit out of the water and let it drain. Reset it in the water to see if it flips completely. {If it does} {When it completely {flips} {rolls} over} replace by {rotating the two cartridges until the arrow on the chlorine cartridge aligns with the unlock symbol on the mineral cartridge and pull apart}. {Follow Step #1 above for attaching a {filled}

{new} chlorine cartridge}.

Do not remove the chlorine cartridge until the system has completely flipped. If the chlorine cartridge {still} contains a small amount of chlorine after the system has {flipped} {rolled} over, place in the {spa} {hot tub} alone until completely empty. Do not allow the chlorine cartridge to sink to the bottom or bleaching of the {spa} {hot tub} surface could occur. When completely empty, discard in trash {or offer for recycling}.

### **Regular {Spa} {Hot Tub} Care**

- Run filtration system as recommended by your {spa} {hot tub} manufacturer or at least 3 hours per day.
- Periodically test water for pH, total alkalinity, calcium hardness and free chlorine levels with the precise Test Strips {that include special directions for using with these products}.
- Maintain {at least a 0.5 ppm} {a} free {active} chlorine level that matches the color shown on the Test Strip bottle {at all times}. {This represents 0.5 to 1.0 ppm.} The SPA CHLORINE DISINFECTANT forms a chlorine bank that is measured as total chlorine on a standard test strip/kit. This chlorine bank readily shifts to {active} {free} chlorine as needed to maintain {a desirable} {our recommended} low level of chlorine {available for disinfection}. {Based on average {spa} {hot tub} usage,} chlorine will last {on average} {about} {up to} {2} {3}-4 weeks for {spas} {hot tubs} {up to} {of} {350} {400} {500} {600} gallons.}
- Shock the {spa} {hot tub} with {granular chlorine or} a non-chlorine shock if the water looks cloudy {and/or add a {spa} {hot tub} clarifier according to label directions}. With SPA CHLORINE DISINFECTANT, far less shocking is required compared to standard water treatments that require weekly shocking or shocking after every use.
- Replace the SPA CHLORINE DISINFECTANT cartridge when the system flips over (see Replacing the Chlorine Cartridge). Replace the complete Floating System every 4 months or when draining and refilling the {spa} {hot tub}. Even if, upon shaking the mineral cartridge, it appears there is spent media left inside, once wetted the time released minerals in the cartridge are effective up to four months.

NOTE: This product may be removed from the {spa} {hot tub} when in use. Lift out of the water and let drain into the {spa} {hot tub}. Then place on {the rail of the {spa} {hot tub} or} {any} surface that is not susceptible to bleaching from the chlorine. Remember to replace the product once exiting the {spa} {hot tub}.

**[All text on this page is optional]**

A perfect companion to {minerals} {reduced chlorine systems}

The chlorine that makes it easy to maintain 0.5 ppm free chlorine.

Don't just use chlorine – use {less!} {chlorine with a {twist} {difference} {distinction}}

The controlled-release chlorine {that's ready when {you need it} {needed}} {that lasts for weeks}

Ideal for high bather loads as chlorine is ready when {you need it} {needed}

A more efficient way to use chlorine {that} {to} disinfect{s} and oxidize{s}

Reduces {free} chlorine use up to 75%\* {when used with Frog minerals}

The low-chlorine solution for Frog mineral systems

SPA CHLORINE DISINFECTANT dissolves slower than standard chlorine products making it easier to maintain a low level, and easier to avoid over chlorination

Reduces the need to shock

No {additional} shocking {needed} {required} before or after {each} {spa} {hot tub} use

Reduces shocking by up to 75%\*\*

Less work with prefilled cartridges, precise output and {fewer} {minimal} shock treatments

The chlorine {that actually helps maintain a neutral pH} {with a built-in pH stabilizer}

{Because} {When} {the} {your} pH {stays} {is} neutral, {the} {your} {free} chlorine is {more effective} {at its best}.

With fewer pH adjustments and less shocking required, SPA CHLORINE DISINFECTANT uses less chemicals than standard {spa} {hot tub} water treatments

Reduces overall chemical use with less shocking and pH adjustments

SPA CHLORINE DISINFECTANT {cartridge} contains chlorine but with a {positive} {beneficial} {innovative} twist

- It reduces the potential for pH decline
- It prevents smelly {chloramine} odors
- It nearly eliminates shocking
- It helps prevent over chlorinating {It lasts longer when used with minerals}

**[All text on this page is optional]**

- {With minerals, it lasts longer}

The SPA CHLORINE DISINFECTANT forms a chlorine bank that is measured using a total chlorine test. This chlorine bank readily shifts to free chlorine as needed to maintain a desirable low level of chlorine available for disinfection.

Unlike {all} other chlorines, there is no need to shock when the total chlorine is {twice the level of} {higher than} the free chlorine. Instead, the chlorine bank, (measured as total chlorine) is waiting to shift to free chlorine as {needed} {it is depleted}. This also allows for the SPA CHLORINE DISINFECTANT {to oxidize odor causing contaminates} {like chloramines}} {to nearly eliminate odor causing contaminates} from your {spa} {hot tub} water.

When testing your water, there is no need to compare the total chlorine level to the free. Simply maintain a low 0.5-1.0 ppm free chlorine at all times. However if you notice your total chlorine dropping, that is a good sign that the cartridge may be getting{nearly} empty.

SPA CHLORINE DISINFECTANT {boosts the concentration of} {super charges} Frog minerals for even greater effectiveness

The {combination} of Frog minerals and SPA CHLORINE DISINFECTANT is very effective in hot water environments as it is easier to maintain a low chlorine level.

#### Mineral System with Smart Chlor

For cleaner, clearer and softer water that cuts the use of chlorine by 75%\*

Each SmartChlor molecule contains 2 chlorine atoms – one for immediate use and one left in reserve to release as {needed} {bather load varies}

The simple science of maintaining a consistent sanitizer level

No peak and valley sanitizing

Smart Chlor creating a {reserve} {bank} of untapped chlorine that continually converts into active chlorine against bacteria

Floating {Sanitizer} {Sanitizing System} for {hot tubs} {spas}

Automatic All-in-One {Hot Tub} {Spa} Care

Complete {Hot Tub} {Spa} Care System

{Creates} Fresh Mineral Water with SmartChlor

{An} innovative slow dissolving mineral system {that destroys bacteria while using {up to 75%\*} less chlorine\* – creating cleaner, clearer and softer water}

1 floating {spa} {hot tub} {sanitizer} {sanitizing system} + {plus} # Test Strips + {plus} {and} # Frog Jump Start {start-up shock}

Fresh Mineral Water {Easy}

An {exclusive} {unique} {proprietary} {innovative} {stand out} water care system from FROG that delivers 4 primary advantages

**[All text on this page is optional]**

Cleaner because it kills bacteria two {2} ways – with minerals and a low level of chlorine

Minerals help keep the pH balanced for Clearer water that shines

Minerals condition the water for Softer effects [feel](#)

Cartridges are pre-filled {for} {no mess, no guess, no stress} making maintenance Easier.

{Learn more at} {For more advantages see} [www.freshmineralwater.com](http://www.freshmineralwater.com)

{Uses} Up to 75%\* less chlorine\* {with no {frustrating} yo-yo chlorine levels}

Cuts chlorine use up to 75%\* while maintaining a constant level

Uses only 25% of normal chlorine levels

Chlorine lasts 3X longer with SmartChlor and FROG Minerals

Shock {only} once a {per} month

The unique SmartChlor technology does the work with far less shocking

Here's a shock – No need for weekly shocking your {hot tub} {spa}

The chlorine that automatically shocks the water for 4 weeks

Self {shocking} {refreshing} {chlorinating} water care system

So little shocking, it's shocking!

Takes the shock out of {hot tub} {spa} care

No shocking the {hot tub} {spa} after each use

{Hot Tub} {Spa} Water Care – for once you're not in for a shock

Making a little chlorine go a long way

Just what you need – and no more

Because less is more

Self regulates for continuous crystal clear water

The unique chlorine reserve goes into action only when needed

The two step chlorine that's time released to meet {hot tub} {spa} demand

When you hop in, SmartChlor goes to work keeping water clean and clear

Easy on {hot tub} {spa} surfaces with less odors

Won't fade swimsuits or dry out skin or hair

Protects your {hot tub} {spa} investment while providing a more enjoyable experience

Easy on your nose

Single color match for easy reading – {exclusively with} {only from} Test Strips

Test Strips – the only sure test for SmartChlor

Simple Go – No Go water testing only from Frog products

The easy test strips only from Frog

**[All text on this page is optional]**

The innovation of SmartChlor

These benefits provided {brought to you} by {the breakthrough technology of} SmartChlor {Technology}.

The chlorine that {reacts} {responds} to {hot tub} {spa} use by maintaining a consistent chlorine level

Unlike normal chlorine that is used up when you get in, SmartChlor continues to maintain the same level

The {vigilant} {proactive} {responsive} {reactionary} chlorine that consistently {sanitizes your water} {keeps your water clean and clear} When you get in, normal chlorine levels drop but SmartChlor remains constant

Fresh Mineral Water Cartridge Lasts 4 months

SmartChlor Cartridge lasts {2}{3}-4 weeks

Floats in the {hot tub} {spa}

Flips over when the SmartChlor cartridge is empty

No adding chlorine daily

No more daily spoon fulls of chlorine

Ditch the daily dosing

Eliminates a cap full a day

No daily maintenance

Stop spoon-feeding your {hot tub} {spa}! {It can take care of itself}

Sporks are for drive-ins, not {spa} {hot tub} care

No measuring, no math, no doubt.

Intelligent water care

You don't have to be a genius to see it's {working} {innovative} {amazing} {smart} {not your ordinary water care} {in a class by itself}

A real breakthrough in {hot tub} {spa} {water} care. A real break for you.

All the clean without all the chlorine

No guesswork. Just less work.

{Hot Tub} {Spa} {water} care doesn't have to be so hard

To find out how you can be more @ease visit [www.{website}](http://www.{website})

Whew, the honey-do-list {your to do list} just got shorter

To find out how you can shorten your honey-do {to do} list visit [www.{website}](http://www.{website})

@ease at your service

**[All text on this page is optional]**

Nicknamed “the butler” our innovative slow dissolving mineral system with SmartChlor for {hot tubs} {spas} will no doubt leave you more at ease  
To find out how you can get your own butler visit [www.{website}](http://www.{website})

Crystal clear {hot tub} {spa} – chemistry degree not required  
@ease is @utomatic

Minerals Destroy Bacteria for less chlorine use  
SmartChlor slowly releases chlorine when needed  
Together they create Fresh Mineral Water that’s Cleaner, Clearer, Softer and Easier

The Mineral Innovation

- Reduces chlorine use up to 75%\*
- Conditions the water for softness
- Easy on {spa} {hot tub} surfaces with less odors
- Lasts four full months

The Breakthrough Science {Technology} of SmartChlor

- Maintains a consistent 0.5 ppm {sanitizer} {disinfectant} {chlorine} level
- Uniquely time released with a chlorine reserve ready when needed
- Easier to test with Test Strips and one color match
- Oxidizes contaminants so far less shocking is required

How {Brand/Product} Works

- The Fresh Mineral Water Cartridge snaps together with the SmartChlor Cartridge
- It floats in the hot tub {spa} and flips over when the SmartChlor Cartridge is empty
- Replace the SmartChlor Cartridge (every {2}{3}-4 weeks) and recycle the empty one

Minerals and SmartChlor completely sanitize any hot tub {spa} with no need for ozone, UV or other devices.

Compatible with ozone {UV} if desired

Start with a freshly filled {hot tub} {spa} or convert any {hot tub} {spa} to Fresh Mineral Water with SmartChlor

No corrosion issues with SmartChlor

Hassle free {hot tub} {spa} sanitization {water care} {maintenance}

Water looks and feels luxurious

SmartChlor isn’t susceptible to big swings in sanitizer levels after use. It maintains a consistent level that just works!

**[All text on this page is optional]**

{Welcome to the} spoon-free zone  
Step into easy  
{Hot tub-life} {Spa-life}. Made easy  
Take it easy on yourself

Easy-does-it

Easy-to-tell

Easy-to-see

Easy-to-use

Easy-to-understand

Easy-to-follow

Easy-to-wow

Easy-to-read

Easy-to-decode

More innovation. Less stress.

More innovation. Less upkeep.

More wows. Less ughs.

The difference between {liking and loving your {spa} {hot tub} {perfect pH and pHew!}  
{green and clean}

How can anything this hard on bacteria feel so soft

Feel the difference

For {Hot Tubs} {Spas}

{Plus} {Also} {Includes} {#} test strips and {#} Jump Start start-up shock  
{Kit} Contains, 1 Pool Frog Mineral Reservoir, 1 SPA CHLORINE DISINFECTANT, 1  
FROG Jump Start start-up shock packet and 1 bottle of # Test Strips

{Kit} Contains, {3} {4} SPA CHLORINE DISINFECTANT Cartridges and {3} {4}  
{maintenance} {non-chlorine} shock packets

3 Replacement {SmartChlor} Cartridges

Product shown is actual size

[Protective Seal Copy]

Remove this {seal} {label} before use. Hold over the {hot tub} {spa} and allow any  
{fines} {particles} to dissolve in the water.

Frog Smart Technology

35 years of water treatment innovation

Yes, it does revolve around you

Relax & Enjoy